



POWER DISTRIBUTION UNIT TIS OUTLET

Product Description

LINK Power Distribution Unit (PDU) can meet the general requirements of power distribution and special demand. Solid, easy installation and modular composite structure are the basic characteristics. Security and stability are our guarantee for the products. The products can meet the installation requirements of 19-inch standard cabinet and non-standard cabinet. More control, outlet standards, accessibility functions can be customized. Applications support datacenter, telecommunications, PC systems, audio video, security, sound and other. Ideal for distribution of UPS, generator or other AC power to protected equipment.

Specifications

Nominal Voltage	: 220 - 250VAC
Frequency	: 50/60Hz
Maximum Amps	: 16A
Maximum Power	: 3,680W
Plug Type	: TIS 166-2549 (16A)
Outlet Type	: TIS 166-2549
Overload protection	: 16A, IEC 60934
Lighting Switch w/Guard	: 16A, EN 61058-1
Surge Current	: 6.5KA
Power Cord Length (m)	: 3m., 5m. and 10m.
Power Cord Electrical Wiring	: 3x1.5mm ² , TIS 11 Part5-2553
Socket material	: PC/ABS (UL94V-0), Black
Panel Material	: Galvanized Steel, Black
Outlet quantity	: 6, 12, & 20 Outlets
PDU Bracket Kit	: Included 1 Pairs
Warranty	: 1 Year
Compliant	: RoHS
IP Rating	: 20
Approval	: TIS.2432-2555
Manufacturer	: ISO 9001:2015



លេខ.2432-2555



Features



TIS Outlet
w/Eye Shutter




TIS 166-2549



Electronic
Circuit Breaker



Lighting Switch
w/Guard



Surge Suppressor

Order Information

Order Number	Description	Dimension (cm) L x W x H
CH-10304A	PDU 4 TIS Outlet w/Cable 3 M. + Lighting SW w/Guard, 16A	39.2 x 5.8 x 4.4
CH-10306A	PDU 6 TIS Outlet w/Cable 3 M. + Lighting SW w/Guard, 16A	49.5 x 5.8 x 4.4
CH-10312A	PDU 12 TIS Outlet w/Cable 3 M. + Lighting SW w/Guard, 16A	79.5 x 5.8 x 4.4
CH-10320A	PDU 20 TIS Outlet w/Cable 3 M. + Lighting SW w/Guard, 16A	118.5 x 5.8 x 4.4