


12 FIBER SPLICING TRAY



DESCRIPTION / APPLICATION

- For use with all LINK rack mount enclosure and wall mount enclosure.
- Made from aluminum and accommodated 12 fusion splicing per tray.
- Protects and manages fiber splices
- Minimum fiber bending radius is maintained
- Used for multimode and single mode




| Part Number | Description | Dimension (mm.) | Color |
|-------------|-------------------------|-----------------|------------|
| SV-2256 | 12 Fiber Splicing Tray | 140 x 125 x 10 | Light Grey |
| SV-2250 | Full Moon Cable Routing | - | Light Grey |

FUSION PROTECTOR SLEEVE

DESCRIPTION / APPLICATION

- For use with splicing tray
- Protects fiber splices
- Clear outer tube and Stainless steel needle.



| Part Number | Description | Dimension (mm.) | Color |
|-------------|---|-----------------|-------|
| SV-2252A | Fusion Splice Protector Sleeve, 60 mm., Slim Type | 2.5 x 60 | Clear |

OTDR DUMMY CABLE BOX

Designed to aid in the testing of fiber optic cable when using an OTDR. Launch Fiber Box is used with Optical Time Domain Reflectometers (OTDR's) to help minimize the effects of the OTDR's launch pulse on measurement uncertainty. Available in many different configurations and fiber lengths.

SPECIFICATION

- Operating Temperature : -40°C to +50°C
 Typical Loss : <1dB@1310nm for 1000 meters
 Standard Attachment : Insert Return Loss Report
 OTDR Test Report
 3D Test Report (Grade A only)



PART NUMBER : UF - [A] - [B] - [C] - [D]

| A = Input Connector | B = Output Connector | C = Fiber | D = Length |
|---------------------|----------------------|--------------------|--------------|
| FC - FC/UPC | FC - FC/UPC | 9 - 9/125 (OS2) | 0.5 - 0.5 km |
| SC - SC/UPC | SC - SC/UPC | 6 - 62.5/125 (OM1) | 1.0 - 1.0 km |
| ST - ST/UPC | ST - ST/UPC | 5 - 50/125 (OM2) | 2.0 - 2.0 km |
| FCA - FC/APC | FCA - FC/APC | 4 - 50/125 (OM3) | - |
| SCA - SC/APC | SCA - SC/APC | - | - |
| LC - LC/UPC | LC - LC/UPC | - | - |

For Example : Single mode fiber, input FC/UPC, output SC/UPC, 1000 meters UF-FC-SC-9-1.0

Remark : Other special fiber or connectors are available upon request.