




STANDARD


- ANSI/TIA-568.2-D Category 5E
- ISO/IEC 11801:2017 Class D
- EN 50173-1 Category 5E
- ICEA S-90-661 Category 5E
- EN 50288-2-1, NEMA WC 63.1
- IEC 61156-5, ASTM D4566-98, IEC 60332-1-2
- UL Listed CM, CMR, CMP and LSZH
- 3P Verified to Category 5E
- UL E197771, RoHS Compliant

APPLICATION

- Structure cabling for horizontal and building backbone
- 2.5G BASE-T (IEEE 802.3bz)
- 10/100/1000 BASE-T (IEEE 802.3i/u/ab)
- IEEE 802.3af/at (PoE/PoE+)
- 52/155/622 Mbps and 1.2 Gbps ATM
- 4/16 Mbps Token Ring
- TP-PMD, TPDDI, ISDN, CDDI, VoIP
- HD BaseT 2.0 standard, Baseband, Broadband
- Digital & Analog for data, video and audio application



US-9035



US-9035PE

ELECTRICAL CHARACTERISTICS

Impedance	: 100±15Ω, 1 MHz to 350 MHz
Mutual Capacitance	: 5.6 nFMax / 100m
Capacitance, Unbalance	: 160 pF Max / 100m
DC Resistance	: 9.38 ohm Max/100m
DC Resistance, Unbalance	: 5% Max.
Insulated Resistance	: 5000 MΩ/Km
Dielectric Strength	: 1kV/min
Propagation Delay	: 536 ns/100m Max @350MHz
Delay Skew	: 25 ns Max

CONSTRUCTION / MATERIAL

Conductor	: 24AWG Solid or Stranded Bare copper
Insulation	CM, CMR, LSZH, OUTDOOR : HDPE CMP : FEP
Mylar	: Mylar Tape
Drain Wire	: Tinned Copper
Shielded	: AL-Mylar Tape
Jacket	CM, CMR : FR-PVC CMP : FR-PVC (Low Smoke) LSZH : FR-LSZH OUTDOOR : UV-Proof, PE

FREQUENCY (MHZ)	INSERTION LOSS (dB/100m)	NEXT MIN.(dB)	ACR-N MIN.(dB)	PS NEXT MIN.(dB)	PS ACR-N MIN.(dB)	ACR-F MIN.(dB/100m)	PS ACR-F MIN.(dB/100m)	RL MIN.(dB)
1	2.0	77	75	75	73	68	65	20.0
25	9.5	56	46.5	54	44.5	40	37	24.3
31.25	10.7	55	44.3	53	42.3	38	35	23.6
62.5	15.4	50	34.6	48	32.6	32	29	21.5
100	19.8	47	27.2	45	25.2	28	25	20.1
155	25.3	44	18.7	42	16.7	24	21	18.8
200	29	43	14	41	12	22	19	18.0
250	32.8	41	8.2	39	6.2	20	17	17.3
300	36.6	40	3.4	38	1.4	18	15	16.8
350	40	39	-	37	-	17	14	16.3

MECHANICAL PROPERTIES

Minimum Bending Radius

Installation 8 X Cable Diameter

Tensile Strength

Operation 4 X Cable Diameter

Ultimate Breaking Strength

110 N (25lbf)

Installation / Operating temperature

>400 N (90lbf)

Storage Temperature

-20°C to 60°C (-40°C to 75°C for Outdoor)

-20°C to 80°C (-40°C to 80°C for Outdoor)

Part No.	UL/NEC Flame Rating	Conductor	Jacket	Diameter (mm.)	Color	Packaging
US-9035	CMR	24AWG Solid Bare Copper	FR-PVC	6.1	White	305m/Reelx
US-9035LSZH	LSZH	24AWG Solid Bare Copper	LSZH	6.1	White	305m/Reelx
US-9035PE	OUTDOOR	24AWG Solid Bare Copper	PE	6.1	Black	305m/Pull Box